



# Installation of Carver by Covercraft® Custom Personal Watercraft Covers

The rear of the cover has the Carver by Covercraft® logo and sewn-on red reflector.

## Sunbrella® & Ultra'tect™ Cover Warranty

### How Long is the Warranty?

This warranty is valid to the original owner for six (6) years from date of purchase for Sunbrella fabric five (5) years for Ultra'tect fabric.

### What is Covered?

Workmanship: Carver by Covercraft will repair any defects in workmanship (including stitching) of the cover. If we cannot repair your cover, we will replace it without charge.

Fabric: Warranty coverage protects against fabric becoming unserviceable due to loss of strength resulting from normal exposure conditions including sunlight, mildew, rot and/or atmospheric chemicals. Covercraft will repair or replace the cover or specific panels judged to be unusable.

### What is NOT Covered?

In continuous outdoor use, fading of fabric color occurs naturally and is not covered by warranty.

### How Long Must You Wait For Replacement?

Your cover will be repaired or replaced and shipped back to you, freight prepaid, within thirty (30) days of Covercraft's receipt of the cover.

### How Can You Get Service?

Call Customer Service at (864) 457-5820, for shipping instructions. Hours are M-F from 8AM to 5PM EST.

### How Does The State Law Apply?

This warranty gives you specific legal rights and you may have additional rights which vary from state to state.

Sunbrella® is a registered trademark of Glen Raven Inc. Ultra'tect™ is a registered trademark of Covercraft Industries, LLC.

©2019 Carver by Covercraft Industries, LLC

**Start at the front** of the watercraft and slide the cover over the nose, making sure the cover is centered.

Move to the back of the watercraft and **pull the cover straight back**, over the body edge usually found above the jet drive. It is a tight fit and you must pull the cover snugly into place. This tight fit prevents flapping or movement while towing.

**NOTE:** If the cover is not tight enough, make the following adjustments with the cover off the watercraft,

- 1) Locate the elastic bungee cord sewn into the hem - you'll find the ends of it at the hem opening at the front of the cover.
- 2) Pull the bungee cord out 4 to 6 inches and tie a new knot past the original knot. **DO NOT** untie the original knot.
- 3) Refit the cover. If it is still not tight enough, repeat step 2 and move the knot further up the cord.

### IMPORTANT TOWING NOTE!

There are two (2) **tie-down loops** on each side of the cover. These must be used to **keep the cover in place while towing**. Use nylon rope or a similar strap through the tie-down loops to securely pull the cover tight under the watercraft. Fasten the tie-down ropes **after the watercraft is loaded** on the trailer. **DO NOT** use rubber or bungee type cords for tie-downs, as they can cause chafing of the watercraft body while trailering.

Watercraft covers have a flap for **access to the fuel filler cap**. This allows you to refuel the watercraft while it is on the trailer, in transit, without removing the cover. **Take care not to spill gasoline** or oil on the cover - it is flammable and will attract dirt and ruin the water repellency.

## CLEANING & CARE INSTRUCTIONS

Clean PWC cover regularly to remove salt, pollen and environmental pollutants that could support the growth of mildew. Brush off any loose dirt or soil, then spray the cover with a solution of mild, non-detergent soap (such as Lux, Dreft, Ivory or Woolite) and cool/warm water. A soft brush may be used on heavily soiled areas; the use of 303 Fabric & Vinyl Cleaner to safely remove dirt and difficult stains from cover is also recommended. If cleaning diminishes the water repellency of the cover, we recommend treating with 303 High Tech Fabric Guard™ Water Repellent. Allow PWC cover to air dry thoroughly before folding for storage.

